

# Photocontrols

## ORDERING INFORMATION



**P105A**

### BASIC MINI-CONTROLS (Button Style)

In sealed case 2-1/8" x 1" x 3/4". 3/8" NPS threaded nipple for use in boxes, fittings and other protective enclosures.

Catalog No.	Volts	Max. Watts Incandescent	Max. Watts HID		Description
			HPF	NPF	
<b>P105A</b>	120	1000	400	250	Black Body
<b>P105M</b>	208-277	1000	400	250	Black Body



**P110A**

### ARCHITECTURAL PENCIL-CONTROLS

Sealed in round plastic case with built-in swivel and 1/2" - 14 NPT arm.

Catalog No.	Volts	Max. Watts Incandescent	Max. Watts HID		Description
			HPF	NPF	
<b>P110A</b>	120	1000	400	250	Black Body



**P150A**

### LIGHT-LEVELER PHOTOCONTROLS

Hermetically sealed polycarbonate with field-adjustable light-leveler and 1/2" nipple.

Catalog No.	Volts	Max. Watts Incandescent	Max. Watts HID		Description
			HPF	NPF	
<b>P150A</b>	120	1800	1000	400	Grey Body
<b>P150M</b>	208-277	1800	1000	400	Grey Body
<b>P150E</b>	480	1800	1000	400	Grey Body
<b>P150F</b>	120-277	1800	1000	400	Grey Body



**P400A**

### TWIST-LOCK PHOTOCONTROLS

Plug-in twist-to-lock controls meet EEI-NEMA standards. Housing high impact butyrate. Temperature range -50°F to +150°F. Surge arrester handles up to 5000V. Built-in 15 second time delay eliminates cycling caused by momentary headlight gleam, lightning flash, etc. P400F universal type for 120V-277V.

Catalog No.	Volts	Max. Watts Incandescent	Max Watts HID		Description
			HPF	NPF	
<b>P400A</b>	120	1800	1000	400	Fiberglass Body
<b>P400E</b>	480	1800	1000	400	Fiberglass Body
<b>P400F</b>	120-277	1800	1000	400	Fiberglass Body

### TWIST-LOCK ACCESSORIES

#### Catalog No. Twist-Lock Accessories

<b>P400R</b>	TWIST-LOCK RECEPTACLE: Polarized molded socket in die-cast aluminum housing with 1/2" male nipple.
<b>P400S</b>	SHORTING CAP: Permits operation of floodlight with photocontrol removed.



UL Wet Location Listed.